



## Data Sheet D 110 C TEXTILE



### RESIN RIBBON FOR FLAT HEAD PRINTER

Prints on nylon, polyester, acetate, etc.  
 Superb smear resistance even at temperature as high as 150°C  
 Image will not blur even with ironing.  
 Printing image durable against water and dry cleaning.



Technical Specifications	
Type:	Resin
Base Film:	Polyester
Base Film Thickness:	4,5 µ
Colour:	Black
Ribbon Transmission Density:	> 1.4
Printing Properties	
Print Speed:	150 mm/s
Ink Melt Point:	83°C
Print Density:	> 1.59 ± 0,2
Standard wash (40°C) ISO C06A1M	ANSI more than B
Standard wash (60°C) ISO C06A1M	ANSI more than B
Usage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Storage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Recommended Media	
Nylon, polyester, acetate, etc.	
Certificate	

TSCA (Toxic Substances Control Act), Directive 76/769/EC; 2003/11/EC; 2000/53/EC, ISO EN71-3, Directive RoHS

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee.  
 Subject to change without notice.

AS-Etikettendrucksysteme GmbH • Gutenbergstraße 36 • 72555 Metzingen  
 Telefon: (+49 71 23) 72 63-0 • Telefax: (+49 71 23) 72 63-22 • E-Mail: info@as-etiketten.de  
 Internet: www.as-etiketten.de