



Data Sheet AS RESIN HEAT RESISTANCE



RESIN RIBBON FOR FLAT HEAD PRINTER

Prints on coated paper, synthetic paper, PE, PET, PP etc.
Excellent smear resistance even at temperature as high as 200°C.
Superior smudge and scratch resistance



Technical Specifications	
Type:	Resin
Base Film:	Polyester
Base Film Thickness:	4,5 µ
Colour:	black
Ribbon Transmission Density:	> 1.0
Printing Properties	
Print Speed:	150 mm/s
Ink Melt Point:	70°C
Print Density:	> 1.7
Abrasion Resistance:	ANSI more than B
Solvent Resistance	ANSI more than D
Usage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Storage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Recommended Media	
coated paper, synthetic paper, PE, PET, PP etc.	
Certificate	
RoHS Directive (2002/95/EC) Conformity	

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.

AS-Etikettendrucksysteme GmbH • Gutenbergstraße 36 • 72555 Metzingen
Telefon: (+49 71 23) 72 63-0 • Telefax: (+49 71 23) 72 63-22 • E-Mail: info@as-etiketten.de
Internet: www.as-etiketten.de