



# Data Sheet AS WAX RESIN NEAR EDGE GOLD



WAX RESIN RIBBON FOR NEAR EDGE PRINTER

Prints on wide variety of substrates, coated and uncoated paper, retail tag, synthetic paper, PE, PET, PP etc.  
High- sensitivity for high-speed printing (250 mm/s). Excellent abrasion resistance.



Technical Specifications	
Type:	Wax Resin
Base Film:	Polyester
Base Film Thickness:	4,5 µ
Colour:	gold, Pantone 971C
Ribbon Transmission Density:	NA
Printing Properties	
Print Speed:	250 mm/s
Ink Melt Point:	72°C
Print Density:	NA
Abrasion Resistance:	ANSI more than B
Solvent Resistance:	ANSI more than C
Usage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Storage Condition	
ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity	
Recommended Media	
Uncoated and coated paper, PE, PET, PP, etc.	
Certificate	
RoHS Directive (2002/95/EC) Conformity	

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.