



Data Sheet AS WAX RESIN RC 2



WAX RESIN RIBBON FOR FLAT HEAD PRINTER

Prints on wide variety of substrates, coated and uncoated paper, retail tag, PE, PET, PP etc.
Excellent smudge and abrasion resistance.



| Technical Specifications | |
|---|------------------|
| Type: | Wax Resin |
| Base Film: | Polyester |
| Base Film Thickness: | 4,5 µ |
| Colour: | Black |
| Ribbon Transmission Density: | > 1.20 |
| Printing Properties | |
| Print Speed: | 200 mm/s |
| Ink Melt Point: | 65°C |
| Print Density: | - |
| Abrasion Resistance: | ANSI more than B |
| Solvent Resistance | ANSI more than C |
| Usage Condition | |
| 5 to 35°C, 30 – 80 % Relative Humidity | |
| Storage Condition | |
| 5 to 35°C, 30 – 80 % Relative Humidity | |
| Recommended Media | |
| coated and uncoated paper, retail tag, PE, PET, PP etc. | |
| Certificate | |
| ISEGA certificate, RoHS Directive (2002/95/EC) Conformity | |

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.