



Data Sheet
TR 6075



RESIN RIBBON FOR FLAT HEAD PRINTER

Prints on coated paper, PE, PET, PVC, PP etc.
High sensitivity for high speed printing up to 200 mm/s.
Extreme durability and solvent resistance



| Technical Specifications | |
|---|------------------|
| Type: | Resin |
| Base Film: | Polyester |
| Base Film Thickness: | 4,5 µ |
| Colour: | Black |
| Ribbon Transmission Density: | 1.4 |
| Printing Properties | |
| Print Speed: | 200 mm/s |
| Ink Melt Point: | 86°C |
| Print Density: | 1.80 |
| Abrasion Resistance: | ANSI more than B |
| Solvent Resistance | ANSI more than B |
| Usage Condition | |
| 5 to 35°C, 30 – 80 % Relative Humidity | |
| Storage Condition | |
| 5 to 35°C, 30 – 80 % Relative Humidity | |
| Recommended Media | |
| coated paper, retail tag, PE, PET, PP, PVC etc. | |
| Certificate | |
| UL recognized, RoHS Directive (2002/95/EC) Conformity | |

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.