



Data Sheet TR 4500



WAX RESIN RIBBON FOR NEAR EDGE PRINTER

Prints on coated/uncoated papers and tags, PE, PET, PP, etc.
High speeds up to 200 mm/s.
High resolution and excellent print density



| Technical Specifications | |
|---|------------------|
| Type: | Wax Resin |
| Base Film: | Polyester |
| Base Film Thickness: | 4,8 µ |
| Colour: | Black |
| Ribbon Transmission Density: | >1.2 |
| Printing Properties | |
| Print Speed: | 200 mm/s |
| Ink Melt Point: | 84°C |
| Print Density: | 1.6 |
| Abrasion Resistance: | ANSI more than A |
| Solvent Resistance | ANSI more than B |
| Usage Condition | |
| ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity | |
| Storage Condition | |
| ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity | |
| Recommended Media | |
| Coated/uncoated paper, retail tag, PE, PET, etc. | |
| Certificate | |
| FDA certificate, RoHS Directive (2002/95/EC) Conformity | |

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.