



Data Sheet
AS WAX RESIN GREEN



WAX RESIN RIBBON FOR FLAT HEAD PRINTER

Prints on wide variety of substrates, coated and uncoated paper, retail tag, synthetic paper, PE, PET, PP etc.



| Technical Specifications | |
|---|------------------------|
| Type: | Wax Resin |
| Base Film: | Polyester |
| Base Film Thickness: | 4,5 µ |
| Colour: | Green, Pantone Green C |
| Ribbon Transmission Density: | N/A |
| Printing Properties | |
| Print Speed: | 200 mm/s |
| Ink Melt Point: | 80°C |
| Print Density: | N/A |
| Abrasion Resistance: | ANSI more than C |
| Solvent Resistance: | ANSI more than C |
| Usage Condition | |
| ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity | |
| Storage Condition | |
| ca. 5 – ca. 35°C, 30 – 80 % Relative Humidity | |
| Recommended Media | |
| Uncoated and coated paper, PE, PET, PP, etc. | |
| Certificate | |
| RoHS Directive (2002/95/EC) Conformity | |

All information on this data sheet are the best currently available. The values may vary slightly when tested in a different environment. The results should, however, only be regarded as general guide to material properties and not as a guarantee. Subject to change without notice.